



- Increases motor life
- Easy to integrate, install and service
- Operates in high ambient temperatures
- High performance and reliability
- Three-year warranty

For motor protection, there is nothing better.

Motor protection and power quality don't have to be a mystery. MTE makes it easy. Case in point: our SineWave Guardian™ Filter. This best-in-class filter delivers unequaled performance in cleaning the PWM waveforms generated by Variable Frequency Drives (VFDs). It virtually eliminates high frequency content and voltage peaks, thereby reducing motor heating to give you extended motor life – and less downtime. The SineWave Guardian also offers incredible reliability and durability. It is more efficient and tolerates higher ambient temperatures, making it ideal for a variety of applications from steel mills to oil fields. Its modular design and smaller footprint make it easier to integrate and install. It all adds up to the best SineWave Filter, and the best value on the market today.



Improve efficiency, improve motor life, and improve your bottom line with our new SineWave Guardian.

SineWave Guardian™ Filters transform the output of Variable Frequency Drives (VFDs) to a near perfect sinusoidal waveform for the best level of motor protection. MTE's unique, patent-pending design offers high performance with smaller size and better efficiency than traditional LC Filters.

Increase motor life: Reduce motor heating through reduction of high frequencies associated with VFD output and also reduce motor insulation stress through reduction of motor peak voltages.

Reduce motor audible noise: Reduce audible noise through reducing high frequencies associated with VFD output.

Reduce radiated emissions: Reduce emissions through reducing high frequencies associated with VFD output.

Protect your motor cable: The reduction of high frequencies associated with VFD output eliminates the need for special motor cables.

Performance Specifications Conventional 3 phase motors operating in volts Service Load Condition per hertz mode, standard step-up transformer optional 380V - 480V +/- 10% Input Voltage 5% maximum @ 2kHz Harmonic Voltage Distortion Inverter Switching Frequency 2kHz to 8kHz 6Hz to 75Hz; >75Hz to Inverter Operating Frequency 120Hz with derating -40C to +60C modular filter Maximum Ambient -40C to +55C enclosed filter Temperature -40C to +90C storage Insertion Loss (Voltage) 6% maximum @ 60Hz Efficiency >98% Altitude Without Derating 3,300 feet above sea level Maximum Motor Lead Length 15,000 feet Relative Humidity 0% to 95% non-condensing 100% RMS continuous: 150% Current Rating for 1 minute intermittent

Final product specifications subject to change at anytime.


SineWave Guardian[™]




Application Configurations:





Extreme Long Lead to Motor





SineWave Guardian Performance:





Without SineWave Guardian

With SineWave Guardian

The SineWave Guardian is a SineWave Filter which protects motors from damage by "cleaning" the sine wave waveform that is generated by the Variable Frequency Drive.



How to properly size your filter

- Determine voltage and frequency requirements
- Reference motor nameplate to determine motor
 HP or KW and Full Load Amps
- Verify motor meets inverter duty standards per NEMA MG1 Section 31
- Select filter based on Motor Full Load Amps

Do not exceed filter's maximum current rating (amps)

• Specify enclosure style

Open (No enclosure)
NEMA 1/2 (General Purpose Enclosure)
NEMA 3R (Outdoor Enclosure)


• Determine derating requirements

Reference Performance Specifications table on previous page as well as derating tables listed below:

Table 1: Drive Output Frequency Derating

Table 2: Altitude Derating Curve

Understanding the SineWave Guardian Part Number:



Derating Curves:




Table 1: Drive Output Frequency Derating




Table 2: Altitude Derating Curve

SINEWAVE GUARDIAN™ SELECTION TABLES

380 - 480V 75Hz															
Motor (Ref Only)		Filter	мте	Enclosure	Filter Dimensions (H x W x D)		Approx Weight		Ref	Watts	Capacitor/Capacitor Panel Assembly Dimensions (H x W x D)		Qty	Ref	
380V KW	480V HP	Amps Rating	Part Number	Туре	Inches	Millimeters	Lbs	Kgs	Fig	Loss		Millimeters	Req'd	Fig	
		2	SWGM0002D	OPEN	4.9 x 4.4 x 2.6	124 x 112 x 66	5	2	7		7.5 x 3.0	191 x 76	1	1	
0.55	0.75		SWGG0002D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	19	9	3	25	-	einstalled in cabinet			
			SWGW0002D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	62	28	5		Pro				
		3	SWGM0003D	0PEN	4.9 x 4.4 x 3.3	124 x 112 x 84	7	3	7		7.5 x 3.0	191 x 76	1	1	
0.75	15.5		SWGG0003D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	21	10	3	45	Preinstalled in cabinet				
			SWGW0003D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	64	29	5		110	- Instatted in Cabinet			
		5	SWGM0005D	OPEN	6.6 x 8.0 x 4.8	168 x 203 x 122	11	5	7		7.5 x 3.0	191 x 76	1	1	
2.2	3		SWGG0005D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	25	11	3	75	Pro	einstalled in cabinet			
			SWGW0005D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	68	31	5			- Translatted in edulinet			
		7	SWGM0007D	OPEN	6.7 x 8.0 x 5.1	170 x 203 x 130	13	6	7	91	7.5 x 3.0	191 x 76	1	1	
3	4		SWGG0007D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	27	12	3		Preinstalled in cabinet				
			SWGW0007D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	61	28	5						
		9	SWGM0009D	OPEN	6.7 x 8.0 x 5.1	170 x 203 x 130	14	6	7		7.5 x 3.0	191 x 76	1	1	
4	5.5		SWGG0009D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	28	13	3	97	Pro	einstalled in cabinet			
			SWGW0009D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	54	24	5			1			
		12	SWGM0012D	0PEN	6.7 x 8.0 x 5.4	170 x 203 x 137	15	7	7	127	7.5 x 3.0	191 x 76	1	1	
5.5	7.5		SWGG0012D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	29	13	3		Preinstalled in cabinet				
			SWGW0012D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	70	32	5			T			
			SWGM0017D	OPEN	7.5 x 9.0 x 4.8	191 x 229 x 122	20	9	7	130	7.5 x 3.0	191 x 76	1	1	
7.5	10	17	SWGG0017D	NEMA 1/2	13.2 x 13.0 x 13.1	335 x 330 x 333	34	15	3		Preinstalled in cabinet				
			SWGW0017D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	76	34	5			1		1	
		22	SWGM0022D	OPEN	8.7 x 10.5 x 6.7	221 x 267 x 170	32	15	7	135	7.5 x 3.0	191 x 76	1	1	
11	15		SWGG0022D	NEMA 1/2	24.0 x 17.0 x 18.5	610 x 432 x 470	79	36	4		Preinstalled in cabinet				
			SWGW0022D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	87	39	5					Т.	
	20	27	SWGM0027D	OPEN	8.7 x 10.5 x 6.7	221 x 267 x 170	35	16	8	1,,,	7.5 x 3.0	191 x 76	1	1	
-			SWGG0027D	NEMA 1/2	24.0 x 17.0 x 18.5	610 x 432 x 470	82	37	4	140	Preinstalled in cabinet				
			SWGW0027D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	90	41	5		7.5 0.0	1 404 00		1 .	
10.5	0.5	35	SWGM0035D	OPEN 1/0	8.9 x 10.5 x 0.0	226 x 267 x 0	39	18	8	210	7.5 x 3.9	191 x 99	1	1	
18.5	25		SWGG0035D	NEMA 1/2	24.0 x 17.0 x 18.5	610 x 432 x 470	87	39	4	210	Pro	einstalled in cabinet			
	İ		SWGW0035D SWGM0045D	NEMA 3R OPEN	24.0 x 12.5 x 22.9	610 x 318 x 582	94	43 18	5 8	-	7 E v 2 0	101 v 00	1	1 1	
22	30	45	SWGG0045D	NEMA 1/2	8.8 x 10.5 x 7.2 24.0 x 17.0 x 18.5	224 x 267 x 183 610 x 432 x 470	90	41	4	225	7.5 x 3.9	191 x 99	'	<u> </u>	
22			SWGW0045D	NEMA 3R	24.0 x 17.0 x 10.3	610 x 318 x 582	98	44	5	1 223	Pro	einstalled in cabinet			
		55	SWGM0055D	OPEN	8.8 x 10.5 x 0.0	224 x 267 x 0	54	24	9	_	8.0 x 3.9	203 x 99	1	1	
- 40	/ ₁ 0		SWGG0055D	NEMA 1/2	24.0 x 17.0 x 18.5	610 x 432 x 470	101	46	4	301	Preinstalled in cabinet				
	10		SWGW0055D	NEMA 3R	24.0 x 12.5 x 22.9	610 x 318 x 582	109	49	5	_					
			SWGM0065D	OPEN	10.7 x 12.0 x 8.6	272 x 305 x 218	59	27	9	_	8.0 x 3.9	203 x 99	1	1	
30	50	65	SWGG0065D	NEMA 1/2	33.9 x 17.8 x 20.9	861 x 452 x 531	136	62	\vdash	310	2.2 % 017			<u> </u>	
-			SWGW0065D	NEMA 3R	33.9 x 17.8 x 26.0	861 x 452 x 660	143	65	6		Pro	einstalled in cabinet			
		80	SWGM0080D	OPEN	10.8 x 12.0 x 9.0	274 x 305 x 229	73	33	9		8.3 x 4.6	211 x 117	1	1	
37	60		SWGG0080D	NEMA 1/2	33.9 x 17.8 x 20.9	861 x 452 x 531	148	67		387	Preinstalled in cabinet				
			SWGW0080D	NEMA 3R	33.9 x 17.8 x 26.0	861 x 452 x 660	154	70	6						
	75	110	SWGM0110D	OPEN	10.7 x 12.0 x 10.5	272 x 305 x 267	105	48	9		8.3 x 4.6	211 x 117	1	1	
55			SWGG0110D	NEMA 1/2	33.9 x 17.8 x 20.9	861 x 452 x 531	180	82	П	395				•	
			SWGW0110D	NEMA 3R	33.9 x 17.8 x 26.0	861 x 452 x 660		85	6		Pro	einstalled in cabinet			

 $Note: Weights \ and \ dimensions \ are \ for \ reference \ only. \ Please \ visit \ \textbf{mtecorp.com} \ for \ detail \ information.$





380 - 480V 75Hz															
Motor (Ref Only)		Filter Amps	MTE	Enclosure	Filter Dimensions (H x W x D)		Approx Weight		Ref	Watts	Capacitor/Capacitor Panel Assembly Dimensions (H x W x D)		Qty	Ref	
380V KW	480V HP	Rating	Part Number	Туре	Inches	Millimeters	Lbs	Kgs	Fig	Loss		Millimeters	Req'd	Fig	
		130	SWGM0130D	OPEN	10.7 x 12.0 x 11.5	272 x 305 x 292	108	49	10		8.3 x 4.6	211 x 117	1	1	
-	100		SWGG0130D	NEMA 1/2	33.9 x 17.8 x 20.9	861 x 452 x 531	182	83	,	6 720					
			SWGW0130D	NEMA 3R	33.9 x 17.8 x 26.0	861 x 452 x 660	189	86	٥		Pre	einstalled in cabinet			
	125	160	SWGM0160D	OPEN	14.5 x 15.3 x 11.3	368 x 389 x 287	160	73	10		6.7 x 16.4 x 7.6	170 x 417 x 193	1	2	
75			SWGG0160D	NEMA 1/2	51.3 x 27.7 x 24.9	1303 x 704 x 632	327	148	6	595	Preinstalled in cabinet				
			SWGW0160D	NEMA 3R	51.3 x 27.7 x 30.0	1303 x 704 x 762	340	154	°		Preinstalled in cabinet				
	150	200	SWGM0200D	OPEN	14.5 x 15.3 x 14.8	368 x 389 x 376	166	75	10	650	6.7 x 16.4 x 7.6	170 x 417 x 193	1	2	
110			SWGG0200D	NEMA 1/2	51.3 x 27.7 x 24.9	1303 x 704 x 632	336	152	6		Dec	einstalled in cabinet			
			SWGW0200D	NEMA 3R	51.3 x 27.7 x 30.0	1303 x 704 x 762	349	158	0		FIE	emstatted in Cabinet			
	200	250	SWGM0250D	OPEN	14.5 x 15.3 x 13.8	368 x 389 x 351	220	100	10		6.9 x 16.4 x 7.6	175 x 417 x 193	1	2	
132			SWGG0250D	NEMA 1/2	51.3 x 27.7 x 24.9	1303 x 704 x 632	381	173	6	775	Preinstalled in cabinet				
			SWGW0250D	NEMA 3R	51.3 x 27.7 x 30.0	1303 x 704 x 762	395	179	Ů		FIE	emstatted in Cabinet			
	250	305	SWGM0305D	OPEN	14.6 x 15.3 x 14.8	371 x 389 x 376	260	118	11	945	7.4 x 16.4 x 7.6	188 x 417 x 193	1	2	
160			SWGG0305D	NEMA 1/2	51.3 x 27.7 x 24.9	1303 x 704 x 632	430	195	6		Pre	einstalled in cabinet			
			SWGW0305D	NEMA 3R	51.3 x 27.7 x 30.0	1303 x 704 x 762	443	201	Ů			- Instatted in cubinet			
	300	365	SWGM0365D	OPEN	14.6 x 15.3 x 15.2	371 x 389 x 386	310	141	11		8.3 x 16.4 x 7.6	211 x 417 x 193	1	2	
200			SWGG0365D	NEMA 1/2	51.3 x 27.7 x 24.9	1303 x 704 x 632	480	218	6	1,050	Pre	einstalled in cabinet			
			SWGW0365D	NEMA 3R	51.3 x 27.7 x 30.0	1303 x 704 x 762	493	224							
	350	415	SWGM0415D	OPEN	14.6 x 15.3 x 15.2	371 x 389 x 386	326	148	11		8.3 x 16.4 x 7.6	211 x 417 x 193	1	2	
220			SWGG0415D	NEMA 1/2	51.3 x 27.7 x 24.9	1303 x 704 x 632	496	225	6 1,13	1,137	Pre				
			SWGW0415D	NEMA 3R	51.3 x 27.7 x 30.0	1303 x 704 x 762	509	231			Preinstalled in cabinet				
	450	515	SWGM0515D	OPEN	15.0 x 15.3 x 16.2	381 x 389 x 411	355	161	12		9.9 x 16.4 x 7.6	251 x 417 x 193	1	2	
280			SWGG0515D	NEMA 1/2	87.6 x 43.7 x 31.1	2225 x 1110 x 790	764	347	6	1,235	Preinstalled in cabinet				
			SWGW0515D	NEMA 3R	87.6 x 43.7 x 40.1	2225 x 1110 x 1019	800	363							
	500	600	SWGM0600D	OPEN	18.3 x 24.0 x 14.6	465 x 610 x 371	483	219	12	2,225	9.9 x 16.4 x 7.6	251 x 417 x 193	1	2	
335			SWGG0600D	NEMA 1/2	87.6 x 43.7 x 31.1	2225 x 1110 x 790	896	406	6		Preinstalled in cabinet				
			SWGW0600D	NEMA 3R	87.6 x 43.7 x 40.1	2225 x 1110 x 1019	932	423						_	
375	600	720	SWGM0720D	OPEN	18.2 x 24.0 x 17.5	462 x 610 x 445	711	323	12	2,300	8.3 x 16.4 x 7.6 9.9 x 16.4 x 7.6	211 x 417 x 193 251 x 417 x 193	1	2	
3/3			SWGG0720D	NEMA 1/2	87.6 x 43.7 x 31.1	2225 x 1110 x 790	1,127	511	,		Davi				
			SWGW0720D	NEMA 3R	87.6 x 43.7 x 40.1	2225 x 1110 x 1019	1,164	528	6		Pre	einstalled in cabinet			
	700	850	SWGM0850D	OPEN	18.2 x 24.0 x 19.0	462 x 610 x 483	835	379	12		7.7 x 16.4 x 7.6	196 x 417 x 193	1	2	
450										2,556	9.9 x 16.4 x 7.6	251 x 417 x 193	2		
			SWGG0850D	NEMA 1/2	84.0 x 52.0 x 36.5	2134 x 1321 x 927	1,473	668	6		Pre	einstalled in cabinet			
			SWGW0850D	NEMA 3R	84.0 x 52.0 x 45.5	2134 x 1321 x 1156	1,514	687			7, 4,, 7,	1 400 /45 400			
E/0	850	1000	SWGM1000D	OPEN	18.1 x 24.0 x 20.6	460 x 610 x 523	942	427	12	2.050	7.4 x 16.4 x 7.6 9.9 x 16.4 x 7.6	188 x 417 x 193 251 x 417 x 193	1	2	
560			SWGG1000D	NEMA 1/2	84.0 x 52.0 x 36.5	2134 x 1321 x 927	1,580	717		2,850	Desirability 12				
			SWGW1000D	NEMA 3R	84.0 x 52.0 x 45.5	2134 x 1321 x 1156	1,621	735	6	,	Pre	einstalled in cabinet			
	1000	1200	SWGM1200D	OPEN	25.7 x 24.0 x 20.3	653 x 610 x 516	1,272	577	13	13	9.9 x 16.4 x 7.6	251 x 416.6 x 193	1	2	
675			SWGG1200D	NEMA 1/2	84.0 x 52.0 x 36.5	2134 x 1321 x 927	1,921	871	L	3,000					
			SWGW1200D	NEMA 3R	84.0 x 52.0 x 45.5	2134 x 1321 x 1156	1962	890	6						
	1200	1500	SWGM1500D	OPEN	25.9 x 24.0 x 20.0	658 x 610 x 508	1,296	588	13	3,210	9.9 x 16.4 x 7.6	251 x 417 x 193	1	2	
800			SWGG1500D	NEMA 1/2	84.0 x 52.0 x 36.5	2134 x 1321 x 927	1,945	882	6		Per	einstalled in cabinet			
			SWGW1500D	NEMA 3R	84.0 x 52.0 x 45.5	2134 x 1321 x 1156	1,986	901			Preinstalled in cabinet				

 $Note: Weights \ and \ dimensions \ are \ for \ reference \ only. \ Please \ visit \ \textbf{mtecorp.com} \ for \ detail \ information.$

SINEWAVE GUARDIAN™ SELECTION TABLES

3-PHASE CAPACITOR













FIGURE 2


CAPACITOR PANEL







ENCLOSURES








FIGURE 3









FIGURE 4

D NOTE: HOODS ONLY ON NEMA 3R ENCLOSURES FIGURE 5



NOTE: HOODS ONLY ON NEMA 3R ENCLOSURES






FIGURE 6



OPEN MAGNETICS










FIGURE 7










FIGURE 8










FIGURE 9










FIGURE 10










FIGURE 11








FIGURE 12

The power quality experts.

MTE Corporation was formed in 1982 by bringing together Milwaukee Transformer Co., Transformer Design Inc., and Milwaukee Electronics Corp. – companies that specialized in different fields of magnetics and transformer designs and were long established in their respective fields. MTE vaulted into a leadership role in power quality with its unique AC reactor design and passive filter expertise. We continued to grow as a global leader with innovative Harmonic Filters, Motor Protection Filters and Sinewave Filters.

Now with the addition of TEAL Electronics in 2016, MTE brings a continuum of power quality solutions unmatched in the industry. Building on TEAL's reputation of high-efficiency transformers and durable power conditioning and distribution units for demanding applications, MTE is building the best power quality company by capitalizing on the individual strength of each while bringing a new dimension in management, marketing, and quality.

Our team of professional design engineers has well over 100 years of collective experience in the industry and is complemented by as much experience in operations. Our engineers utilize state-of-theart platforms and best-in-class simulation/modeling tools so that new designs meet your needs and the latest compliance standards while improving your bottom line.

At MTE, we know power quality because power quality is all we do.

A Handy & Harman company. Better together.

Handy & Harman Ltd. (NASDAQ:HNH) is a diversified manufacturer of engineered niche industrial products with leading market positions in many of the markets it serves. Through its wholly-owned operating subsidiaries, HNH focuses on high margin products and innovative technology and serves customers across a wide range of end markets. HNH's diverse product offerings are marketed throughout the United States and internationally.









MTE Corporation N83 W13330 Leon Road Menomonee Falls WI 53051 (800) 455-4MTE • (262) 253-8200

Menomonee Falls, WI • San Diego, CA • Singapore • Xianghe • Tecate • Mexicali