NIC@R[®] LED Paragon

3" DDA SPECIFICATION GRADE DOWNLIGHT



M	ax	Lm	V	V

95-100 1500 15 3" 2200 21 80-100

*See spec sheet for more details

CCT











HOUSING

ADJ, Remodel, New Construct



LOCATION

Wet / Damp Location

TRIM SHAPE

Round, Square

TRIM COLOR

White, Black, Specular Clear

Smooth, Baffle

QUIET CEILING

Round, Square, None

CRI 80, 90



Beam Patterns



Lm/W


































APPLICATIONS

Residential Homes, Exterior, Hospitality, Retail and Malls



NIC@R[®] LED Paragon

4", 6", 8", & 10" SPECIFICATION GRADE DOWNLIGHT



W **Max Lm**

	1900	16
4-10"	2800	25
STANDARD	4370	38
	5650	50
6-10"	7200	70
HIGH OUTPUT	9300	100
v.c	1	1



^{*}See spec sheet for more details

CCT









DIM TO WARM 1.8-3.0k

¹Dim to warm only available in 16-38W

HOUSING ICAT, Remodel, Architectural, **New Construction**

SIZES

4", 6", 8", 10"

TRIM COLOR

White, Black, Specular Clear,

Haze, Champagne, Wheat

FLANGE COLOR

White, Self, Flangeless, Custom

QUIET CEILING Round, None

CRI

80, 90

OPTIC





Beam Patterns







²Only available as 4" option

³Onlý 20° and 40° optics available for 70W & 100W light engines

APPLICATIONS

Office Buildings, Commercial Spaces, Institutional, Health Care

